



COMFORT COMES IN ALL SHAPES AND SIZES

High Wall Mini-Split System with easy-to-use remote control capability



LENNOX

Innovation never felt so good.™

60Hz System Air conditioner and heat pump Performance Specifications

Air Conditioner

Outdoor Model			KF25-09C-GW-E	KF35-12C-GW-E	KF51-18C-GW-E	KF70-24C-GW-E	KF88-30C-GW-E	
Indoor Model			KF25-09C-GW-C	KF35-12C-GW-C	KF51-18C-GW-C	KF70-24C-GW-C	KF88-30C-GW-C	
Voltage			220/60HZ/1PH					
Nominal Cooling Capacity	[BTU]		9000	12000	18000	24000	30000	
Cooling Ampacity	[A]		4.3	5.5	8.7	11.8	17.2	
EER	[BTU/W]		9.57	10.17	9.52	9.64	8.36	
Max. Power Input	[W]		1,250	1,500	2,300	3,260	4,790	
Cooling Power Input	[W]		940	1,180	1,890	2,490	3,590	
Indoor Unit	Air Flow		450	500	650/800	1100	1250	
	Noise Level	m2/h	dB (A)	29-42	35-42	41-50	46-50	46-50
	Power Input		[W]	40	40	60	100	100
	Unit Dimensions H x W x L		[mm]	745 x 250 x 195	745 x 250 x 195	900x 292 x 215	1000 x 320 x 200	1225 x 330 x 245
Outdoor Unit	Net/Gross Weight		Lbs	22/29	22/29	40/48	44/53	44/53
	Compressor Type			Rotary				
	Noise Level		dB (A)	55	58	60	60	60
	Power Input		[W]	900	1140	1830	2390	3490
Ref. Piping	Unit Dimensions H x W x L		[mm]	700 x 225 x 500	795 x 255 x 510	795 x 255 x 540	870 x 310 x 700	900 x 330 x 835
	Net/Gross Weight			77/84	77/84	110/154	110/154	110/154
	Liquid Line		in	1/4	1/4	3/8	3/8	3/8
	Suction Line		in	3/8	1/2	5/8	5/8	5/8
	Max. Ref. Pipe Length		ft	33	33	50	50	50
	Max. Ref. Vertical Length		ft	16,4	16,4	16,4	16,4	16,4

Heat Pump

Outdoor Model			KF25-09C-GW-E	KFR35-12C-GW-E	KFR51-18C-GW-E	KFR70-24C-GW-E	KFR88-30C-GW-E	
Indoor Model			KFR25-09C-GW-C	KFR35-12C-GW-C	KFR51-18C-GW-C	KFR70-24C-GW-C	KFR88-30C-GW-C	
Voltage			220/60HZ/1PH					
Nominal Cooling Capacity	[BTU]		9000	12000	18000	24000	30000	
Cooling Ampacity	[A]		4.4	5.4	8.7	11.7	16.3	
EER	[BTU/W]		9.47	10.26	9.68	9.64	8.85	
Heating Capacity	[W]		2,700	3,700	5,610	7,300	9,500	
COP			3.00	3.22	3.11	3.13	2.92	
Heating Power Input			900	1,130	1,800	2,330	3,250	
Heating Ampacity	[A]		4.2	5.0	8.5	11.0	15.3	
Max. Power Input	[W]		1,300	1,600	2,300	3,270	4,630	
Cooling Power Input	[W]		950	1,170	1,860	2,490	3,390	
Indoor Unit	Air Flow		450	500	650/800	1100	1250	
	Noise Level	m2/h	dB (A)	29-42	35-42	41-50	46-50	46-50
	Power Input		[W]	40	40	60	100	100
	Unit Dimensions H x W x L		[mm]	745 x 250 x 195	745 x 250 x 195	900x 292 x 215	1000 x 320 x 200	1225 x 330 x 245
Outdoor Unit	Net/Gross Weight		Lbs	22/29	22/29	40/48	44/53	44/53
	Compressor Type			Rotary				
	Noise Level		dB (A)	55	58	60	60	60
	Power Input		[W]	900	1140	1830	2390	3490
Ref. Piping	Unit Dimensions H x W x L		[mm]	700 x 225 x 500	795 x 255 x 510	795 x 255 x 540	870 x 310 x 700	900 x 330 x 835
	Net/Gross Weight			77/84	77/84	110/154	110/154	110/154
	Liquid Line		in	1/4	1/4	3/8	3/8	3/8
	Suction Line		in	3/8	1/2	5/8	5/8	5/8
	Max. Ref. Pipe Length		ft	33	33	50	50	50
	Max. Ref. Vertical Length		ft	16,4	16,4	16,4	16,4	16,4



© Lennox Industries Inc. 2012

Visítenos en www.Lennox.com o comuníquese con nosotros al 1-800-9-LENNOX.